

App'n. No. 10/840,039

Attorney Docket No. 10541-1998

## I. Amendments to the Claims

1. (Currently Amended): A system to compensate for luminance degradation of a display, the system comprising:

a controller coupled to the display and configured to provide power to the display thereby controlling the display luminance; and

a temperature sensor proximate the display and in electrical communication with the controller, wherein the controller is configured to vary the display luminance, based on a temperature measured by the temperature sensor, wherein the controller is configured to decrease the display luminance as the temperature of the display increases through a first temperature range until the temperature reaches an upper temperature threshold.

2. (Cancelled).

3. (Currently Amended): The system according to claim 1, wherein after the temperature reaches the upper temperature threshold the controller is configured to increase the display luminance as the temperature of the display decreases through the first temperature range to a lower temperature threshold.

4. (Original): The system according to claim 1, wherein the controller is configured to vary the display luminance based on a transfer function having a linear term.

5. (Original): The system according to claim 4, wherein the controller is configured to vary the display luminance based on the relationship  $L_{OP} = m \cdot T_K + b$ .

BRINKS  
HOFFER  
GILSON  
BLTONE

-2-

Appln. No. 10/840,039

Attorney Docket No. 10541-1998

where  $L_{OP}$  is the display luminance,  $m$  is a gain,  $T_K$  is the temperature of the display, and  $b$  is an offset.

6. (Previously Presented): The system according to claim 1, wherein the controller is configured to define a second temperature range and vary the luminance of the display through the first temperature range based on the temperature of the display.

7. (Original): The system according to claim 6, wherein the controller is configured to control the luminance of the display to remain a constant value over the second temperature range.

8. (Original): The system according to claim 7, wherein a lowest temperature of the first range is between 20° and 30° C.

9. (Original): The system according to claim 6, wherein the luminance is at about 100% of full power luminance at the lowest temperature of the first range.

10. (Original): The system according to claim 9, wherein the luminance is at about 50% of the full power luminance at between 80° and 90° C.

11. (Original): The system according to claim 6, wherein the display luminance in the first temperature range is varied by a transfer function having a linear component.

BRINKS  
HOFFER  
DILSON  
& LIGONE

Appln. No. 10/840,039

Attorney Docket No. 10541-1998

12. (Original): The system according to claim 11, wherein the display luminance is varied based on the relationship  $L_{OP} = m \cdot T_K + b$ , where  $L_{OP}$  is the display luminance,  $m$  is a gain,  $T_K$  is the temperature of the display, and  $b$  is an offset.

13. (Original): The system according to claim 1, wherein the display luminance is varied based on a luminance degradation function.

14. (Original): The system according to claim 13, wherein the display luminance is varied based on a transfer function having an inversely proportional relationship to the luminance degradation function.

15. (Currently Amended): A method for compensating luminance degradation of an OLED display, the method comprising:

providing power to the OLED display;

measuring a temperature of the OLED display;

varying luminance of the OLED display based on the temperature of the OLED display; and

decreasing the display luminance as the temperature of the OLED display increases through a first temperature range until the temperature reaches an upper temperature threshold.

16. (Cancelled).

BRINKS  
HOFFER  
GILSON  
ELIONE

-4-

Appln. No. 10/840,039

Attorney Docket No. 10541-1998

17. (Currently Amended): The method according to claim 15 increasing the display luminance as the temperature of the OLED display decreases through the first temperature range to a lower temperature threshold, after the temperature reaches the upper temperature threshold.

18. (Original): The method according to claim 15, wherein the display luminance is varied based on a transfer function having a linear term.

19. (Original): The method according to claim 16, wherein the display luminance is varied based on the relationship  $L_{OP} = m \cdot T_K + b$ , where  $L_{OP}$  is the display luminance,  $m$  is a gain,  $T_K$  is the temperature of the OLED display, and  $b$  is an offset

20. (Previously Presented): The method according to claim 15, further comprising defining a second temperature range and varying the luminance of the OLED display over the first temperature range based on the temperature of the OLED display.

21. (Original): The method according to claim 20, further comprising controlling the luminance of the OLED display to remain a constant value over the second temperature range.

22. (Original): The method according to claim 21, wherein the lowest temperature of the first range is between 20° and 30° C.

BRINKS  
HOFFER  
GILSON  
ALDRINE

Appln. No. 10/840,039

Attorney Docket No. 10541-1998

23. (Original): The method according to claim 20, wherein the luminance is at 100% of the full power luminance at the lowest temperature of the first range.

24. (Original): The method according to claim 21, wherein the luminance is at about 50% of the full power luminance at between 80° and 90° C.

25. (Original): The method according to claim 20, wherein the display luminance is varied by a transfer function having a linear component.

26. (Original): The method according to claim 25, wherein the display luminance is varied based on the relationship  $L_{OP} = m \cdot T_K + b$ , where  $L_{OP}$  is the display luminance,  $m$  is a gain,  $T_K$  is the temperature of the OLED display, and  $b$  is an offset.

27. (Original): The system according to claim 16, wherein the display luminance is varied based on a luminance degradation function.

28. (Currently Amended): A system to compensate for luminance degradation of an OLED display, the system comprising:

a controller coupled to the OLED display and configured to provide power to the OLED display thereby controlling the display luminance; and

a temperature sensor proximate the OLED display and in electrical communication with the controller, wherein the controller is configured to vary the display luminance, based on a temperature measured by the temperature sensor; wherein the controller is configured to decrease the display luminance as the

DRINKS  
HOFFER  
GILSON  
ELTONE

Appln. No. 10/840,039

Attorney Docket No. 10541-1998

temperature of the OLED display increases through a first temperature range until the temperature reaches an upper temperature threshold.

29. (Cancelled).

30. (Currently Amended): The system according to claim 28, wherein after the temperature reaches the upper temperature threshold the controller is configured to increase the display luminance as the temperature of the OLED display decreases through the first temperature range to a lower temperature threshold.

31. (Original): The system according to claim 28, wherein the controller is configured to vary the display luminance based on a transfer function having a linear term.

32. (Original): The system according to claim 31, wherein the controller is configured to vary the display luminance based on the relationship  $L_{OP} = m \cdot T_K + b$ , where  $L_{OP}$  is the display luminance,  $m$  is a gain,  $T_K$  is the temperature of the OLED display, and  $b$  is an offset

33. (Previously Presented): The system according to claim 28, wherein the controller is configured to define a second temperature range and vary the luminance of the OLED display over the first temperature range based on the temperature of the OLED display.

BRINKS  
HOFFER  
GILSON  
KLIDNE

Appl. No. 10/840,039

Attorney Docket No. 10541-1998

34. (Original): The system according to claim 33, wherein the controller is configured to control the luminance of the OLED display to remain a constant value over the second temperature range.

35. (Original): The system according to claim 34, wherein a lowest temperature of the first range is between 20° and 30° C.

36. (Original): The system according to claim 33, wherein the luminance is at about 100% of full power luminance at the lowest temperature of the first range.

37. (Original): The system according to claim 36, wherein the luminance is at about 50% of the full power luminance at between 80° and 90° C.

38. (Original): The system according to claim 33, wherein the display luminance in the first temperature range is varied by a transfer function having a linear component.

39. (Original): The system according to claim 38, wherein the display luminance is varied based on the relationship  $L_{OP} = m \cdot T_K + b$ , where  $L_{OP}$  is the display luminance,  $m$  is a gain,  $T_K$  is the temperature of the OLED display, and  $b$  is an offset.

40. (Original): The system according to claim 28, wherein the display luminance is varied based on a luminance degradation function.

BRINKS  
HOFFER  
GILSON  
ALTONA

Appln. No. 10/840,039

Attorney Docket No. 10541-1998

41. (Original): The system according to claim 40, wherein the display luminance is varied based on a transfer function having an inversely proportional relationship to the luminance degradation function.

BRINKS  
HOFFER  
GILSON  
BLIGNE

-9-